



IMPORTANT NOTES

- THIS CHECKLIST IS FOR CAGELESS SS CARS ONLY.** ALL CAGED SS CARS MUST MEET ALL NASCC ICE RACE SUPPLEMENTAL REGULATIONS AS DOCUMENTED.
- CARS SHALL COMPLY TO ALL SUPPLEMENTAL REGULATIONS.** IF THEY AREN'T LISTED HERE BUT ARE IN THE SUPP REGS, YOUR CAR MUST COMPLY TO THEM.
- DON'T FORGET THE GOLDEN RULE,** THE ANSWER TO THE QUESTION "CAN I DO X TO MY CAR?" IS NO, UNLESS IT IS LISTED IN THE SUPPLEMENTAL REGULATIONS.

HOW TO USE

Check each item that you comply with, fix those you do not. Make sure you read the supplemental regulations, this checklist covers the critical points, but is not perfect.

VEHICLE

WHEELBASE & WEIGHT - Car weighs 3,150 LBS or less and does not exceed 110 inch wheelbase.

LAYOUT – Vehicle is a non-convertible car and is FWD, RWD, or AWD

WHEELS AND TIRES

TIRE TYPE – commercial, DOT "Winter" tire, non-studded, 165 minimum width – *Blizzaks, Hakkapeliittas, Michelin X-ice are banned*

WHEEL – any non-space saver wheel

TIRE COST – shall not exceed \$160 a tire retail price (tirerack.com CAD)

TRACTIONIZING – tires shall be tractionized using the club tractionizer only, once per season

INTERIOR

SUNROOF – disabled, securely, see rules

WINDOWS – factory, must remain, closed at all times while racing. Windshield is factory, glued in, no cracks.

CRASH PROTECTION & METAL – all factory crash protection and factory metal must remain, no removal permitted

ROLLCAGE – not required, but encouraged, caged vehicles must meet all NASCC ice race rules.

BALLAST – not permitted

SEATS – OE seats are OK, aftermarket seats are also OK.

SEATBELTS – OE 3-point required in cageless cars, 5-point not permitted. Caged cars must run 5-point (see NASCC supp regs).

MIRRORS – minimum 1 internal rearview mirror

AIRBAGS – all airbags must be physically removed

LOOSE ITEMS – cars must not have loose items in the interior that can roll around, remove them. Air fresheners must be Hello Kitty only (this bit of humor meant to ensure you read this).

DRIVER & PASSENGER SAFETY

HELMET - Minimum Snell 2015 M OR ECE R22.05/22.05 with cage; Snell M2010 or newer, Snell SA2010 or newer without cage

FRONTAL HEAD RESTRAINT (HANS) – Not permitted.

CLOTHING - Fire Resistant (FR) coveralls made of Nomex, Proban, or equal CSA rating.

MECHANICAL

STEERING & SUSPENSION – must remain stock. Factory swaybars allowed.

EXHAUST – modifications permitted, must exit outside bodywork, behind driver

ENGINES & TRANSMISSIONS – swaps allowed, encouraged to remain stock (horsepower doesn't matter in rubber to ice racing)

BRAKES – required on all 4 wheels

BATTERY – factory mounted, min 2 points mechanical tiedown, positive terminal insulated

FUEL TANKS / FUEL SYSTEM – must remain factory stock, even if engine swapped.

RADIATOR / COOLING – mods permitted, factory stock recommended.

KILLSWITCH – recommended, not required

EXTERIOR

BODY – Cars must be neat & clean, no structural rust or large body damage. Body must remain stock. No aftermarket Aero.

LIGHTING – headlights, taillights, brake lights, and rear facing high-mount 20W fog lamp required

WINDSHIELD WIPERS – must be functional

MIRRORS – minimum 2 external mirrors

CAR DECALS – including car numbers and class decals adhere to NASCC supp reg norms.